

GMA-JACK6-BK

Keystone Connector, Category 6, Black.

Specifications & Features

- Compact slim design fits into any conventional face plate, outlet box, or panel.
- IDC insetion life 200 cycles.
- Plug insertion life 750 cycles Min.
- Dielectric strength no change, when applied AC 750V or DC 1000V 1 minute between adjancet terminal.
- Category 6 keystone jack 180°.
- Slimline shape design for high-density applications.
- Enhanced IDC termination towers reduce installation time and increased performance

Material Specifications

Body Color: Blue, Red, White, Black
 Body Material: High-Impact Fire Retardant Plastic
 Contact Base Material: Phosphor Bronze
 Contact Sub-Surface Material: 100 microinches thick Nickel - Plated
 Contact Surface Material: 50 microinches thick Gold - Plated



GMA-JACK6-BK

Mechanical Specifications

Cable Type: 8 Conductor Utp Copper Cat 5e, 6, 6A
 Connector Feature: Channel/Component Rated
 Position/Conductor: 8P8C
 Termination Type: 110 Puchdown
 Wiring Standard: T568A - T568B

Available Colors:



Standards and Certifications

FCC: Part 68 Compliant
 NEC: Article 800 Compliant
 TIA/EIA: TIA-568B

Dimensions:

